

COP Test
Six Panel Door Painting
Open Book Format

1. Properly installed hardware should have _____ paint on it.
2. The vertical pieces of wood excluding the panels are called _____.
3. The horizontal pieces of wood excluding the panels are called _____.
4. _____ is a sticky cloth used to remove fine dust particles.
5. The areas of the door that are recessed from the surface are called _____.
6. A _____ could be used to check if the tops and bottoms of a door have been painted.
7. The production rate on a door is approx. _____ per side.
8. When painting the panels, paint the _____ and _____ first.
9. Using a _____ will help to speed up the application of the paint.
10. You should paint the _____ and _____ of a door to slow down expansion and contraction and to meet door manufacturer's warranty requirements.
11. What is a holiday? _____

12. What is hiding? _____

13. What is the basic general difference between Materials & Supplies AND Tools & Equipment. _____

14. List 5 Standard Personal Tools

_____, _____, _____
_____, _____

15. List at least 2 Standard Job Site Tools

_____, _____

16. Name two items that can be used to hold a door open while painting.

_____, _____

17. Before painting the door, make sure the _____ has been removed and/or properly protected.

18. After the top and bottom edges have been painted, the next edge to paint is the

_____.

19. Always brush in the direction of the wood _____.

20. After all the panels have been painted the first stile and rail to be painted are #'s

_____ and _____.